

SMALL, InGaAs CAMERA FOR SHORT EXPOSURES

Xenics
EXOSENS GROUP

Bobcat 320 Gated Series



SMALL InGaAs CAMERA FOR SHORT EXPOSURES

KEY FEATURES



FLEXIBLE AND EASY TO USE



COMPACT AND LIGHTWEIGHT



HIGH FRAME RATE OF UP TO 400 Hz

The Bobcat 320 Gated series is based on an in-house developed, temperature stabilized InGaAs detector with a 320 x 256 pixel resolution. The Bobcat 320 Gated cameras are able to provide maximum frame rates up to 400 Hz.

The exposure time of the sensor is configurable from 100 ns up to 1 ms in steps of 100 ns, or from 1 ms to 40 ms. The camera comes with either a CameraLink or GigE Vision interface.

Bobcat 320 Gated Series



KEY PERFORMANCES

Image format / Pixel pitch	320 x 256 pixels/ 20 μ m
Detector type	InGaAs photodiode array with CTIA ROIC
Sensor temperature stabilization	TE cooler
Integration type	Snapshot - global shutter
Spectral range	900 - 1700 nm
Max frame rate (full frame)	400 Hz
Power consumption	2.8 W (no TE cooler) or 4 W (no TE cooler)
Power supply voltage	DC 12 V

FUNCTIONS & INTERFACES

Command and control	CameraLink or GigE Vision
Connector trigger	SMA
Camera dimensions (width x height x length)	55 mm x 55 mm x 72 mm or 55 mm x 55 mm x 82 mm
Optical interface	C-mount or M42
Camera weight	285 gr or 334 gr

PRODUCT SELECTOR GUIDE

XEN-000585 (Bobcat 320 CL Gated)	XEN-000525 (Bobcat 320 GigE Gated)
----------------------------------	------------------------------------

advancedimaging@exosens.com



exosens.com

EXOSENS
REVEAL THE INVISIBLE